


Material: Messing roh
Einsatztemperatur: -40°C / +300°C
Einsatzbereich: Löt- oder steckbar 6,3 x 1,0 mm


Material: Brass
Temperature range: -40°C / +300°C
Application: Solderable or pluggable 6,3 x 1,0 mm



zu Anschlussgewinde metrisch

suitable for metric entry thread

Art.-Nr.	 G	D1 mm	D2 mm	 mm	
1012.80.10	M12	13.0	24	1	100
1017.80.10	M16	16.5	24	1	100
1020.80.10	M20	20.5	28	1	100
1025.80.10	M25	25.5	32	1	100
1032.80.10	M32	33.0	40	1	100
1040.80.10	M40	40.5	52	1	100
1050.80.10	M50	50.5	62	1	50
1063.80.10	M63	63.5	78	1	50



zu Anschlussgewinde Pg

suitable for entry thread Pg

Art.-Nr.	 G	D1 mm	D2 mm	 mm	
1007.80.10	Pg 7	13.0	24	1	100
1009.80.10	Pg 9	16.0	24	1	100
1011.80.10	Pg 11	19.0	28	1	100
1013.80.10	Pg 13	21.0	28	1	100
1016.80.10	Pg 16	23.0	32	1	100
1021.80.10	Pg 21	29.0	37	1	100
1029.80.10	Pg 29	38.0	52	1	50
1036.80.10	Pg 36	48.0	62	1	50