



Material: CrNi Stahl A2
(DIN EN 1.4305 / AISI 303)
O-Ring : NBR
Einsatztemperatur: -40°C / +100°C
Schutzart: IP 68

Material: CrNi stainless steel A2
(DIN EN 1.4305 / AISI 303)
O-ring : NBR
Temperature range: -40°C / +100°C
Protection class: IP 68

Kurzes Anschlussgewinde metrisch mit O-Ring

Short entry thread metric with O-ring

Art.-Nr.	G	Ø mm	H mm	L mm	
8710.96.08.70	M10x1.5 ¹⁾	12	3	5	50
8712.96.08.70	M12x1.5	14	3	5	50
8717.96.08.70	M16x1.5	19	3	5	50
8720.96.08.70	M20x1.5	24	3	6	25
8725.96.08.70	M25x1.5	28	4	7	25
8732.96.08.70	M32x1.5	35	4	8	10
8740.96.08.70	M40x1.5	45	6	8	10
8750.96.08.70	M50x1.5	55	6	9	10
8763.96.08.70	M63x1.5	70	6	10	10
8775.96.08.70	M75x1.5	80	6	11	5

1) Metrisches Regelgewinde

1) Metric coarse-pitch thread

Langes Anschlussgewinde metrisch mit O-Ring

Long entry thread metric with O-ring

Art.-Nr.	G	Ø mm	H mm	L mm	
8710.96.11.08.70	M10x1.5 ¹⁾	12	3	10	50
8712.96.11.08.70	M12x1.5	14	3	10	50
8717.96.11.08.70	M16x1.5	19	3	10	50
8720.96.11.08.70	M20x1.5	24	3	10	25
8725.96.11.08.70	M25x1.5	28	4	11	25
8732.96.11.08.70	M32x1.5	35	4	13	10
8740.96.11.08.70	M40x1.5	45	6	13	10
8750.96.11.08.70	M50x1.5	55	6	14	10
8763.96.11.08.70	M63x1.5	70	6	15	10
8775.96.11.08.70	M75x1.5	80	6	15	5

1) Metrisches Regelgewinde

1) Metric coarse-pitch thread

Auf Anfrage lieferbar:
Anschlussgewinde Pg

On request:
Entry thread Pg